

THEIA[®] Blade / Hybrid Exit Sign

ABN 12629158069



FEATURES:

- ✓ **Sizes** 16M, 24M
- ✓ **Fully Compliant** to Australian Codes
- ✓ **Environmentally Safe & Sustainable**
- ✓ **Ideal for Office, Retail and Commercial**
- ✓ **Simple & Effective**

CONTACT

A Level 5/15 Queen St
Melbourne VIC 3000

P +61 (3) 7004 7500
1300 244 569

E support@safetypath.com

W www.safetypath.com

LED REQUIREMENTS

Theia Blade Exit Signs are available as either PL only (Blade) or PL+LED (Hybrid Blade) versions.

A minimum of 100 Lux is required at the face of the PL only exit sign.

LED Hybrid options are applicable for low lighting environments where the illumination is less than 100 lux at the face of the exit sign.

NCC COMPLIANCE

Safety Path PL Exit Signs are designed in accordance and compliant with Building Code of Australia, NCC Specification E4.8.

All relevant documentation shall be made available upon request.

MAINTENANCE

The following maintenance (inspection) regime for PL exit signs may be undertaken by any competent person.

For Hybrid signs that have an LED component, the light panel or PSU should be replaced when it expires.

Six Monthly:

- ✓ Survey to ensure signs are in place, legible, not obstructed and shall be cleaned as necessary.
- ✓ Survey to ensure the general building light sources are operational and have had no unauthorised alterations.
- ✓ Survey to ensure the LED component on any Industrial Hybrid signs are functioning correctly and remain illuminated with the presence of mains power connected to the signs.

Three Yearly:

- ✓ Test to ensure signs receive the minimum illumination requirement from the general building light sources or our LED component.
- ✓ The illumination at the face of the sign should be checked with an illuminance meter.





Diagram: Based on 24m Theia Hybrid Exit Sign

SPECIFICATIONS

Voltage	240v ~50hz
Connection	2 pin plug Aus/NZ
Power	16m - .55 watts 24m - 1.3w
IP Rating	IP20
Dimensions	16m - 303mm x 193mm x 16mm 24m - 433mm x 258mm x 16mm
Material	Case - Acrylic Top cap - Steel Internals - Polycarbonate
Pictorials	1 x Left 1 x Right 2 x Neutrals
Warranty	7 years
Compliance	NCC Specification E4.8 AS2293.1 (Relevant PL Clauses) AS3000 (cl 1.9.32)
Viewing Distance	16m or 24m
Mounting Type	Ceiling Mount Recessed Suspended Wall Mount
Weight	16m - 2kgs 24m - 3.5kgs

PRODUCT RANGE



Theia Blade Exit Sign (PL)


Code	Description	Direction
EC16SSN	16m SS NEUTRAL	Single Sided Neutral (Straight Ahead)
EC16SSL	16m SS LEFT	Single Sided Left Arrow
EC16SSR	16m SS RIGHT	Single Sided Right Arrow
EC16DSN	16m DS NEUTRAL	Double sided Neutral (Straight ahead)
EC16DSD	16m DS DIRECTIONAL	Double Sided Directional
EC24SSN	24m SS NEUTRAL	Single Sided Neutral (Straight Ahead)
EC24SSL	24m SS LEFT	Single Sided Left Arrow
EC24SSR	24m SS RIGHT	Single Sided Right Arrow
EC24DSN	24m DS NEUTRAL	Double sided Neutral (Straight ahead)
EC24DSD	24m DS DIRECTIONAL	Double Sided Directional

Theia Hybrid Blade Exit Sign (LED)


Code	Description	Direction
ECL16SSN	16m SS NEUTRAL	Single Sided Neutral (Straight Ahead)
ECL16SSL	16m SS LEFT	Single Sided Left Arrow
ECL16SSR	16m SS RIGHT	Single Sided Right Arrow
ECL16DSN	16m DS NEUTRAL	Double sided Neutral (Straight ahead)
ECL16DSD	16m DS DIRECTIONAL	Double Sided Directional
ECL24SSN	24m SS NEUTRAL	Single Sided Neutral (Straight Ahead)
ECL24SSL	24m SS LEFT	Single Sided Left Arrow
ECL24SSR	24m SS RIGHT	Single Sided Right Arrow
ECL24DSN	24m DS NEUTRAL	Double sided Neutral (Straight ahead)
ECL24DSD	24m DS DIRECTIONAL	Double Sided Directional

MOUNTING OPTIONS


Suspended



Ceiling Mounted



Wall Mounted



*Hybrid Blade versions shown

